



CONDUITS ICTA 3422 ORANGE

Ø 50



STF50



ATF50



50



40,09



25



**CONDUITS ISOLANTS
CINTRABLES,
TRANSVERSALEMENT
ANNELÉS.**



**PROTECTIVE INSULATING
CONDUITS CORRUGATED,
PLIABLE.**

NORMES

NA CEI 61386 .1
NA CEI 61386.22

RÉSISTANCE À L'ÉCRASEMENT

Classe 3, Médium (plus de 750 N sur 5cm à $23 \pm 2^{\circ}\text{C}$)

RÉSISTANCE AU CHOCS

Classe 4, lourde (6 joules à -5°C)

TEMPÉRATURE MINIMALE D'EXERCICE

Classe 2 (-5°C)

TEMPÉRATURE MAXIMALE D'EXERCICE

Classe 2 ($+90^{\circ}\text{C}$)

RÉSISTANCE À LA PROPAGATION DE LA FLAMME

Propagateur de flamme (Test d'inflammabilité non applicable)

RÉSISTANCE ÉLECTRIQUE D'ISOLEMENT

Plus de 100 mohm (tension de 500 V pour 1 minute)

RIGIDITÉ DIÉLECTRIQUE

Plus de 2000V à 50Hz pendant 15 minutes

STANDARDS

NA CEI 61386.1
NA CEI 61386.22

COMPRESSION RESISTANCE

Class 3 Medium (higher than 750 N on 5cm at $23 \pm 2^{\circ}\text{C}$)

IMPACT RESISTANCE

Class 4, Heavy (6 joules at -5°C)

MINIMUM TEMPERATURE RANGE

Class 2 (-5°C)

MAXIMUM TEMPERATURE RANGE

Class 2 ($+90^{\circ}\text{C}$)

FLAME PROPAGATION RESISTANCE

Flame Propagator (Flammability Test Not Applicable)

ELECTRIC INSULATING RESISTANCE

Higher than 100 mohm for 500V in 1 minute

DIELECTRIC STRENGTH

Higher than 2000V at 50Hz for 15 minutes